



# Ruggedized NTU

## Model 2701R

The Patton Model 2701R NTU terminates E1 and Fractional E1 services and provides conversion to V.35, X.21, EIA-530 and 10Base-T Ethernet.

### Wall or DIN Rail Mount

Easily installs into any environment

### Connect to Any Terminal Interface

Smooth clock V.35, X.21, EIA-530, and 10Base-T Ethernet interfaces

### Connect at Any Speed

Select nx64 data channels, or 2-Mbps Clear Channel

### Eliminate Routers

Bridge Ethernet across the WAN using industry standard PPP/BCP

### Standalone or Rack Solutions

Available in desktop and high density SNMP managed racks

### Power It Anywhere

Universal input AC (100-240V) and -48 VDC power supply options

One of the smallest and most economical NTUs available, the Model 2701R is designed with features usually found in more expensive units: flexible clocking modes, AMI/HDB3 coding, V.52/V.54 diagnostics, and user-selectable nx64 kbps data rates.

The Model 2701R series terminates E1/FE1 services for all nx64 kbps to 2.048 Mbps rates and connects to a router, FRAD, CODEC, or LAN with V.35, X.21, EIA-530, or 10Base-T interfaces. Front facing LEDs and easily accessible switches allow for instant diagnostics

and service monitoring. Convenient DIP switches support quick and concise configuration of your E1 termination. AC or DC power options make installing the Model 2701R into your network infrastructure a *snap*.

The wide variety of features, compact size, and low price make Patton's Ruggedized E1 NTUs the right solution for your next network challenge.

Visit [www.patton.com](http://www.patton.com) for more information.



Special Rates Available  
Call for Details



Model 2701



Model 2701RC

Standalone and 2U-high rack card versions are available with the same features as the ruggedized 2701R.

Easily accessible switches for loops and test patterns

LEDs display network, data, and diagnostic status at-a-glance



Power from universal AC inputs or -48 VDC

10Base-T connector (RJ-45)

G.703 interface (RJ-48C)

## Why use our E1 NTUs?

### Key Features

Supports full 2 Mbps or nx64 kbps

V.35, X.21, EIA-530, or 10Base-T Interfaces

Built-in V.54/V.52-compliant diagnostics. Responds to CO initiated loops

Available in DIN, wall mount, desktop, or high density SNMP managed racks

100–240 VAC or –48 VDC power options

### Benefits/Advantages

E1 service flexibility. Pay only for the data you use.

Flexible interface options mean the Model 2701R will easily connect to your network

Diagnose problems on the spot, thereby ensuring network reliability and up-time

Higher density in smaller spaces with command and control over your network

Universal power supply options make installing the Model 2701R into your network infrastructure a *snap!*

*The model 2701's price, variety of interfaces and features make it the right solution for your E1 network!*

## NetLink™ 2701R Product Family



	2701R/C 2701/C	2701R/B 2701/B	2701R/D 2701/D	2701R/I 2701/I	2701RC/A/I	2701RC/B/B	2701RC/D/V	2701RC/D/D	2701RC/C/I
DCE Interface	V.35	EIA-530	X.21	10Base-T	V.35	EIA-530	X.21	X.21	10Base-T
Network Interface	RJ-48C		RJ-48C & Dual BNC		RJ-48C			Dual BNC	RJ-48C
Power Supplies	UI (100–240 VAC) or -48 VDC				AC or DC rack power supplies				
Dimensions	1.50 H x 4.17 W x 5.84 D inch (3.84 H x 10.6 W x 14.84 D cm)				3.0 H x 0.83 W x 7.84 D inch (7.6 H x 2.1 W x 19.0 D cm)				
Weight	1.0 lbs (0.45 kg)				0.31 lbs (0.14 kg)				
Line Rate	2.048 Mbps (E1 and Fractional E1)								
Line Coding	AMI or HDB3								
Line Framing	G.703 (unframed) or G.704/G.732 (framed)								
DTE Rates	nx64 kbps (V.35, EIA-530, X.21/V.11); nx64 kbps to 10Base-T (10 Mbps)								
Clocking	Smooth clocking—Internal, External or Receive Recover								
Diagnostics	Local/Remote Loop, 511 and 511E BERT								
Range	1.6 km								
Compliance	CE Mark, G.703, G.704, G.723, G.832, CTR-12 and CTR-13; 1500 VRMS transformer isolation								
Temperature/Humidity	32 to 122°F (0 to 50°C)/5 to 90% relative humidity, non-condensing								

07MD2701R-DS2

Patton is a registered trademark, and NetLink is a trademark of Patton Electronics Company in the United States and other countries.



Meriedweg 7  
CH-3172 Niederwangen  
Phone +41 (31) 985 25 25  
Fax +41 (31) 985 25 26  
E-mail [sales@inalp.com](mailto:sales@inalp.com)  
Web [www.inalp.com](http://www.inalp.com)



7622 Rickenbacker Drive  
Gaithersburg, MD 20879 USA  
Phone +1-301-975-1000  
Fax +1-301-869-9293  
E-mail [sales@patton.com](mailto:sales@patton.com)  
Web [www.patton.com](http://www.patton.com)